

NEW FROM SOLAX X1-BOOST G4



X1-BOOST G4

2.5kW / 3.0kW / 3.3kW / 3.6kW
4.2kW / 5.0kW / 6.0kW

Features

Superior Performance

- DC Input: 200% oversizing, 16A current, 50V startup voltage
- In-built global MPP scan for higher yield efficiency

User Friendly Monitoring

- 10s level interval of data update (Optional, new WiFi dongle required)
- Quick and easy configuration (WiFi & APP)

Assured Safety & Reliability

- AC/DC built-in Type II SPD (Optional) and I-V curve diagnosis supported
- Optional external RSD (Rapid Shutdown) and integrated DC AFCI protection (Optional)
- In-built export control function

Superb Adaptability

- Home EV Charger and Heat Pump Solution adaptable
- Mass management and broad extension via Datahub
- Master/Slave parallel solution via Modbus supported

info@solaxpower.com
service@solaxpower.com



+61 1300 476529 support@solaxpower.com.au

www.solaxpower.com.au



V1.3. Information may be subject to modify without notice.
Exclusive for SolaX Power Australia

DC INPUT

Max. PV array input power [Wp]	6000	6000	6600	7200	8000	10000	12000
Max. PV input voltage [V]	600	600	600	600	600	600	600
Startup voltage [V]	50	50	50	50	50	50	50
Nominal input voltage [V]	360	360	360	360	360	360	360
MPP tracker voltage range [V]	40~560	40~560	40~560	40~560	40~560	40~560	40~560
No. of MPP trackers / String per MPP tracker	2 / 1						
Max. PV input current[A]	16 / 16						
Isc PV Array Short Circuit current [A]	22 / 22						

AC OUTPUT

Rated AC output power [W]	2500	3000	3300	3680	4200	5000 ^①	6000
Rated AC output apparent power (VA)	2500	3000	3300	3680	4200	5000 ^①	6000
Rated AC output current [A]	10.9	13.1	14.4	16	18.3	21.7	26.1
Max. AC output apparent power [VA]	2750	3300	3630	4048 ^④	4620	5000 ^②	6000
Max. AC output current [A]	12	14.4	15.8	17.6 ^⑤	20.1	21.7 ^③	27.3
Nominal AC voltage / AC voltage range [V] **	220/230/240;90~290						
Nominal AC frequency / AC frequency range [Hz] **	50/60;±5						
Power Factor range	0.8leading~0.8lagging						
THDi (rated power) [%]	<3						

SYSTEM DATA

Max. Efficiency [%]	98						
Euro. Efficiency [%]	97						
Standby consumption [W] @Night	<3						
Ingress protection	IP66						
Operating ambient temperature range [°C]	-25~60						
Max. operation altitude [m]	4000						
Relative humidity [%]	0~100						
Typical noise emission [dB]	25 ^⑥						
Storage temperature [°C]	-30~70						
Dimensions (W x H x D) [mm]	404x274x146						
Weight [kg]	11						
Cooling concept	Nature cooling						
Communication interfaces	USB/RS485/DRM, Optional: Meter/CT *						
Optional monitoring dongle	Pocket WiFi/LAN/4G						
Display	2 x LED + LCD (16 x 2) / APP						

PROTECTION

Over / under voltage protection	Yes						
DC isolation protection	Yes						
Monitoring ground fault protection	Yes						
Grid monitoring	Yes						
DC injection monitoring	Yes						
Back feed current monitoring	Yes						
Residual current detection	Yes						
Anti-islanding protection	Yes						
Over temperature protection	Yes						
SPD (DC/AC)	Type II / Type II (Optional)						
Arc-fault circuit interrupter (AFCI)	Optional						
AC auxiliary power supply (APS)	Optional						
DC Switch	Yes						

STANDARD

Safety	IEC / EN 62109-1 / -2						
EMC	EN61000-6-1 / 2 / 3 / 4, EN61000-3-2 / 3 / 11 / 12						
Certification	IEC61727, EN50549, G98/G99, AS 4777.2, VDE4105, CEI 0-21, VFR, PPDS, TOR						

① 5000 (4600 for VDE4105, 4999 for AS4777.2) ② 5000 (4600 for VDE4105, 4999 for AS4777.2) ③ 21.7 (20 for VDE4105) ④ 4048 (3680 For G98/G99, TOR and PPDS) ⑤ 17.6 (16 For G98/G99, TOR and PPDS)
 ⑥ For models with internal fan(Optional), typical noise emission is 30 dB
 * Not included in the package. Please purchase additionally. ** The AC voltage and the frequency range may vary from different country codes.