

Sigen Energy Controller

3.0 – 12.0 kW | Single Phase
 5.0 – 30.0 kW | Three Phase
 5.0 – 12.0 kW | Three Phase Low Voltage



- EMS-integrated intelligent management for precision control
- Max. 2.0 DC/AC ratio compatibility, higher energy utilization (Single Phase)
- Unbalanced 3-phase power output, ensuring efficient operation
- 150% peak output power in off-grid mode, instant high-power boost
- Up to 4 MPP trackers for maximum solar energy extraction

Sigen Energy Controller 3.0–12.0 kW Single Phase ¹

SigenStor EC	3.0 SP	3.6 SP	4.0 SP	4.6 SP	5.0 SP	6.0 SP	8.0 SP	10.0 SP	12.0 SP	Units	
DC Input (from PV)											
Max. PV power	6000	7360	8000	9200	10000	12000	16000	20000	24000	W	
Max. DC input voltage										600	V
Nominal DC input voltage										350	V
Start-up voltage										100	V
MPPT voltage range										50 ~ 550	V
Number of MPP trackers	2						3	4	4		
Number of PV strings per MPPT										1	
Max. input current per MPPT										16	A
Max. short-circuit current per MPPT										20	A
AC Output (on-grid)											
Nominal output power	3000	3680	4000	4600	5000	6000	8000	10000	12000	W	
Max. output apparent power	3300	3680	4400	5000	5500	6600	8800	11000	12000	VA	
Nominal output current	13.6	16.0	18.2	20.9	22.7	27.3	36.4	45.5	54.6	A	
Max. output current	15.0	16.0	20.0	22.7	25.0	30.0	40.0	50.0	54.6	A	
Nominal output voltage							220 / 230 / 240		220 / 230		V
Nominal grid frequency										50 / 60	Hz
Power factor										0.8 leading ~ 0.8 lagging	
Total current harmonic distortion										THDi < 2%	
Efficiency											
Max. efficiency	98.0%	98.0%	98.0%	98.0%	98.0%	98.0%	97.6%	97.6%	97.6%		
European efficiency	97.0%	97.1%	97.2%	97.3%	97.4%	97.4%	97.0%	97.0%	97.0%		
AC Output (backup)											
Peak output power (10 seconds)	4500	5520	6000	6900	7500	9000	12000	15000	15000	W	
Nominal output voltage							220 / 230 / 240		220 / 230		V
Nominal output frequency										50 / 60	Hz
Power factor										0.8 leading ~ 0.8 lagging	
Total voltage harmonic distortion										THDv < 2%	
Disruption time of backup switch ²										0	ms
Battery Connection											
Battery module models										SigenStor BAT series	
Number of modules per controller										1 ~ 6	pcs
Battery module voltage range										300 ~ 600	V
Protection											
Safety protection feature										DC reverse polarity protection, Insulation monitoring, Residual current monitoring, Arc fault circuit interrupter ³ , AC overcurrent/overvoltage/short-circuit protection. Type II DC/AC surge protection, Anti-islanding protection	
General Data											
Dimensions (W / H / D)							700 / 300 / 245		700 / 300 / 260		mm
Weight							18		36		kg
Storage temperature range										-40 ~ 70	°C
Operating temperature range										-30 ~ 60	°C
Relative humidity range										0% ~ 100%	
Max. operating altitude										4000	m
Cooling							Natural convection		Smart air cooling		
System ingress protection rating										IP66	
Communication										WLAN / Fast Ethernet / RS485 / Sigen CommMod (4G/3G/2G)	
Standard Compliance											
Standard ⁴										IEC/EN 62109-1, IEC/EN 62109-2, IEC/EN 61000-6-1, IEC/EN 61000-6-2	

1. Sigen Energy Controller 8.0-12.0 kW Single Phase is only available in specific regions. Please contact Sigenenergy or local distributors for details.
 2. This refers to the load-side disruption time, to achieve this functionality Sigen Energy Gateway needs to be used together with Sigen Energy Controller and Sigen Battery. Test conditions: In the open-circuit state of the power grid, the nominal power of the Sigen Energy Controller is higher than the total power of the home loads.
 3. This is an optional feature only supported in certain models, please contact Sigenenergy for more information.
 4. For all standards refer to the certificates category on the Sigenenergy website.

Sigen Energy Controller 5.0–30.0 kW Three Phase ¹

SigenStor EC	5.0 TP	6.0 TP	8.0 TP	10.0 TP	12.0 TP	15.0 TP	17.0 TP	20.0 TP	25.0 TP	30.0 TP	Units	
DC Input (from PV)												
Max. PV power	8000	9600	12800	16000	19200	24000	27200	32000	40000	48000	W	
Max. DC input voltage											1100	V
Nominal DC input voltage											600	V
Start-up voltage											180	V
MPPT voltage range											160 ~ 1000	V
Number of MPP trackers	2		3			4						
Number of PV strings per MPPT											1	
Max. input current per MPPT											16	A
Max. short-circuit current per MPPT											20	A

AC Output (on-grid)												
Nominal output power	5000	6000	8000	10000	12000	15000	17000	20000	25000	30000	W	
Max. output apparent power	5500	6600	8800	11000	13200	16500	18700	22000	27500	33000	VA	
Nominal output current	7.6	9.1	12.2	15.2	18.2	22.8	25.8	30.4	38.0	45.5	A	
Max. output current	8.4	10.0	13.4	16.7	20.1	25.1	28.4	33.4	41.8	50.0	A	
Nominal output voltage											380 / 400, 3W+N+PE	V
Nominal grid frequency											50 / 60	Hz
Power factor											0.8 leading ~ 0.8 lagging	
Total current harmonic distortion											THDi < 2%	

Efficiency											
Max. efficiency	98.1%	98.2%	98.3%	98.3%	98.3%	98.3%	98.3%	98.3%	98.3%	98.4%	
European efficiency	96.1%	96.6%	97.1%	97.5%	97.7%	97.9%	97.9%	97.9%	98.0%	98.0%	

AC Output (backup)												
Peak output power (10 seconds)	7500	9000	12000	15000	18000	22500	25500	30000	30000	36000	W	
Nominal output voltage											380 / 400, 3W+N+PE	V
Nominal output frequency											50 / 60	Hz
Power factor											0.8 leading ~ 0.8 lagging	
Total voltage harmonic distortion											THDv < 2%	
Disruption time of backup switch ²											0	ms

Battery Connection												
Battery module models											SigenStor BAT series	
Number of modules per controller											1 ~ 6	pcs
Battery module voltage range											600 ~ 900	V

Protection											
Safety protection feature	DC reverse polarity protection, Insulation monitoring, Residual current monitoring, Arc fault circuit interrupter ³ , AC overcurrent/overvoltage/short-circuit protection, Type II DC/AC surge protection, Anti-islanding protection										

General Data												
Dimensions (W / H / D)											700 / 300 / 260	mm
Weight											36	kg
Storage temperature range											-40 ~ 70	°C
Operating temperature range											-30 ~ 60	°C
Relative humidity range											0% ~ 100%	
Max. operating altitude											4000	m
Cooling											Smart air cooling	
System ingress protection rating											IP66	
Communication											WLAN / Fast Ethernet / RS485 / Sigen CommMod (4G/3G/2G)	

Standard Compliance											
Standard ⁴	IEC/EN 62109-1, IEC/EN 62109-2, IEC/EN 61000-6-1, IEC/EN 61000-6-2										

- ¹ Sigen Energy Controller 30.0 kW Three Phase is only available in specific regions. Please contact Sigenenergy or local distributors for details.
- ² This refers to the load-side disruption time, to achieve this functionality Sigen Energy Gateway needs to be used together with Sigen Energy Controller and Sigen Battery. Test conditions: In the open-circuit state of the power grid, the nominal power of the Sigen Energy Controller is higher than the total power of the home loads.
- ³ This is an optional feature only supported in certain models, please contact Sigenenergy for more information.
- ⁴ For all standards refer to the certificates category on the Sigenenergy website.

Sigen Energy Controller 5.0–12.0 kW Three Phase Low Voltage ¹

SigenStor EC	5.0 TPLV	6.0 TPLV	8.0 TPLV	10.0 TPLV	12.0 TPLV	Units	
DC Input (from PV)							
Max. PV power	8000	9600	12800	16000	19200	W	
Max. DC input voltage						600	V
Nominal DC input voltage						360	V
Start-up voltage						100	V
MPPT voltage range						50 ~ 550	V
Number of MPP trackers	2	2	3	3	4		
Number of PV strings per MPPT						1	
Max. input current per MPPT						16	A
Max. short-circuit current per MPPT						20	A

AC Output (on-grid)							
Nominal output power	5000	6000	8000	10000	12000	W	
Max. output apparent power	5500	6600	8800	11000	13200	VA	
Nominal output current	13.2	15.8	21.0	26.2	31.5	A	
Max. output current	14.5	17.4	23.1	28.9	34.7	A	
Nominal output voltage						220 / 230	V
Nominal grid frequency						50 / 60	Hz
Power factor						0.8 leading ~ 0.8 lagging	
Total current harmonic distortion						THDi < 2%	

Efficiency						
Max. efficiency						98%
European efficiency	97.3%	97.5%	97.7%	97.8%	97.8%	

Battery Connection							
Battery module models	SigenStor BAT series						
Number of modules per controller	1 ~ 6						pcs
Battery module voltage range	300 ~ 600						V

Protection						
Safety protection feature	DC reverse polarity protection, Insulation monitoring, Residual current monitoring, Arc fault circuit interrupter ² , AC overcurrent/overvoltage/short-circuit protection, Type II DC/AC surge protection, Anti-islanding protection					

General Data							
Dimensions (W / H / D)						700 / 300 / 260	mm
Weight						36	kg
Storage temperature range						-40 ~ 70	°C
Operating temperature range						-30 ~ 60	°C
Relative humidity range						0% ~ 100%	
Max. operating altitude						4000	m
Cooling						Smart air cooling	
System ingress protection rating						IP66	
Communication						WLAN / Fast Ethernet / RS485 / Sigen CommMod (4G/3G/2G)	

Standard Compliance						
Standard ³	IEC/EN 62109-1, IEC/EN 62109-2, IEC/EN 61000-6-1, IEC/EN 61000-6-2					

- ¹ Sigen Energy Controller Three Phase Low Voltage is only available in specific regions. Please contact Sigenenergy or local distributors for details.
- ² This is an optional feature only supported in certain models, please contact Sigenenergy for more information.
- ³ For all standards refer to the certificates category on the Sigenenergy website.

Disclaimer: The information in this file is provided on an "as is" basis. To the fullest extent permitted by law, Sigenenergy Technology Co., Ltd. excludes all representations and warranties relating to this file and its contents or which is or may be provided by any affiliates or any other third party, including in relation to any inaccuracies or omissions in this file.