

580W-600W

ME-120

21.23%
MAXIMUM EFFICIENCY

120
HALF CELLS

- ◆ Established durability and yield data
- ◆ High flexibility with BOM




Ver. 26.1.1

30 YEARS
Performance Warranty

up to **30 YEARS***
Product Warranty

*The regular product warranty is 15 years, please refer to the latest version of AESOLAR Limited Warranty for the duration of the product warranty under special conditions. For extensions, please contact AESOLAR staff.

OUR PERFORMANCE WARRANTY



LID RESISTANT



PID RESISTANT



SALT CORROSION RESISTANT



SAND RESISTANT



AMMONIA RESISTANT






HIGHLY STABLE AND TOUGH

AE ME-120 580W-600W

P-TYPE PERC TECHNOLOGY

MONO-FACIAL PV MODULE



Electrical specifications (STC*):


Parameter	P_{max} (Wp)	580	585	590	595	600
Nominal max. power	P_{max} (Wp)	580	585	590	595	600
Maximum operating voltage	V_{MPP} (V)	33.60	33.80	34.00	34.20	34.40
Maximum operating current	I_{MPP} (A)	17.26	17.31	17.35	17.40	17.44
Open-circuit voltage	V_{oc} (V)	40.70	40.90	41.10	41.30	41.50
Short-circuit current	I_{sc} (A)	18.25	18.37	18.42	18.47	18.52
Module efficiency	η (%)	20.52	20.70	20.87	21.05	21.23
Power tolerance	(W)			0~+5		
Maximum system voltage	(V)			1500		
Maximum series fuse rating	(A)			30		

*STC: Standard Test Conditions (irradiance 1000 W/m², cell temperature 25°C and air mass of AM1.5), measurement tolerance P_{max} : ±3%

Mechanical and design specification

Cell type	Gallium-doped mono c-Si PERC, half-cut cells
No. of cells	120
Front cover	3.2 mm glass, high transmission, AR coated, tempered
Encapsulation	EVA
Back cover	White backsheet
Junction box	IP68 rated, 3 bypass diodes
Frame	30 mm anodized aluminium alloy
Cable (Including Connector)	1 x 4 mm ² , 350 mm length or customized
Connectors	MC 4 / MC 4 compatible
Dimension	2171 mm x 1302 mm x 30 mm
Weight	29 kg
Hail resistance	Max. Ø 25 mm at 23 m/s
Wind load	2400 Pa or 244 kg/m ²
Snow load	5400 Pa or 550 kg/m ²

Packaging information



Temperature ratings

Operating temperature	-40 to +85°C
Temp. coefficient of P_{max}	-0.34 %/°C
Temp. coefficient of V_{oc}	-0.25 %/°C
Temp. coefficient of I_{sc}	0.040 %/°C
Nom. operating cell temp. NOCT	43 ± 2°C

Electrical specifications (NMOT*):

Parameter	P_{max} (Wp)	436	440	444	448	452
Nominal max. power	P_{max} (Wp)	436	440	444	448	452
Maximum operating voltage	V_{MPP} (V)	31.60	31.80	32.00	32.20	32.40
Maximum operating current	I_{MPP} (A)	13.81	13.85	13.88	13.92	13.95
Open-circuit voltage	V_{oc} (V)	37.90	38.10	38.30	38.50	38.70
Short-circuit current	I_{sc} (A)	14.56	14.70	14.74	14.78	14.82

*NMOT: Normal Module Operating Temperature (irradiance 800 W/m², ambient temperature 20°C, air mass of AM1.5 and wind speed of 1 m/s)

SYSTEM AND PRODUCT CERTIFICATIONS



IEC 61215 IEC 61730
Regular Production Surveillance
www.tuv.com

IEC 62716 (Ammonia corrosion)
IEC 61701 (Salt mist corrosion)
IEC 60068 (Sand and dust)
IEC 62804 (PID resistance)

The specifications and characteristics contained in this datasheet may deviate slightly from our actual products due to the product developments and uncertainty of measurement devices. The specifications included in the datasheet are subject to change without prior notice.